

Ricoh Priport JP 5000

| | |
|--|---|
| BACKGROUND INFORMATION | 11899/USA |
| Dataquest Segment | NA |
| SRP | \$12,355 |
| Manufacturing Status | Discontinued (08/2002) |
| Domestic Intro Date | December 1998 |
| OEM | Ricoh (Japan) |
| Also Sold As | Gestetner CopyPrinter 5450; Savin 3350DNP; Standard SD400 |
| Distributed By | Dealers, branches and subsidiaries |
| Max Monthly Duty Cycle | 400,000 impressions |
| TYPE | Digital duplicator, MF |
| Configuration/Scanner | Desktop,digital |
| Toner | Ink technology |
| GENERAL SPECIFICATIONS/PAPER HANDLING | |
| First Copy Time | 12 sec |
| Multicopy (Ltr/Lgl/Ldgr) | 60 to 120/60 to 120/60 to 120 cpm |
| Warm-up Time | None |
| Std Paper Source(s) | Single tray |
| Std Paper Capacity | 1,000 sheets |
| Paper Weights | 13-lb bond to 110-lb index |
| Bypass/Paper Weights | None |
| Max Paper Sources | 1 |
| Max Paper Capacity | 1,000 sheets |
| Max Original Size | 12 x 17 |
| Output Size (Min/Max) | 3-1/2 x 5-13/16/12-13/16 x 17-5/8 |
| Copy Resolution | 400 x 400 dpi |
| Copier Memory (Std/Max) | Not applicable |
| Duplex | Manual |
| Duplex Capacity/Paper Sizes | Not applicable |
| Document Feeder | Opt ADF |
| Doc Feeder Speed/Capacity | Not applicable/30 orig |
| Paper Weights | 13 to 34 lbs |
| Sorter (Bins/Capacity) | None |
| Staple Sorter | None |
| Bins/Stapling Capacity | Not applicable |
| Stapling Positions | Not applicable |
| Finisher | None |
| Tray/Stapling/Position(s) | Not applicable |
| Other | |
| SECURITY SPECS | |
| Network User Authentication | Info not avail |
| IP Address Filtering | Info not avail |
| MAC Address Filtering | Info not avail |
| HDD Overwrite | Info not avail |

| | |
|-------------------------------|---|
| Max Overwrites | Info not avail |
| HDD Encryption | Info not avail |
| Secure Print | Info not avail |
| Other | |
| CONTROL PANEL | Keypad |
| Quantity Selector | 1 to 9,999 (0 to 9 keypad) |
| Message Display | Yes, four lines |
| Help Key | No |
| FEATURES | |
| Automatic Features | AES, AMS, APS |
| Book Copy | No |
| Booklet Mode | No |
| Color | Opt |
| Copy Control | 20 |
| Covers | No |
| Editing | Opt |
| Energy-Save | Yes |
| Erase | Std |
| Image Insert | No |
| Image Overlay | Opt |
| Image Repeat | No |
| Image Rotate | Std |
| Interrupt | No |
| Job Build | No |
| Job Programs | 9 |
| Job Time | No |
| Language | No |
| Margin Shift | Yes |
| Neg/Pos | No |
| OHP Interleaving | No |
| Photo Mode | Yes |
| Poster Mode | No |
| Preset R/E | 4R,3E |
| Program Ahead | No |
| Sheet Insertion | No |
| Stamping | Opt |
| Timer | No |
| 2-in-1 | No |
| XY Zoom | Yes |
| Zoom Range | 50 to 200 (1%) |
| Other Features | Auto line/photo separation mode; manual image density control; preset and batch memory; original background correction; halftone modes; max print area, 11.4" x 16.5"; pencil mode; center, edge and shadow erase; economy mode |
| ADDITIONAL INFORMATION | |
| Dimensions (HxWxD) | 56" x 26" x 23" |
| Weight | 207 lbs |
| Power Requirements | 120 V, 4.5 A |
| Dedicated Outlet | Not required |
| Energy Star Compliant | No |
| Operating Noise Level | 60 dB |

| | |
|------------------------------------|---|
| COMMENTS | Platen-type duplicator; options include color drum, ADF, computer interface for Macintosh and Windows, editing and cabinet; 11 colors avail (incl black); dual cylinder system improves registration & print quality; std tapeless separation device; *200/315 mstrs/roll; auto master sizing |
| OPTIONS | |
| | ADF: \$1,313 Editing: \$1,004 Cabinet: \$305 Color drum unit "L": \$1,313 Color drum unit "S": \$1,313 |
| MAINTENANCE | |
| Fuser Rollers | Not applicable |
| Yield | Not applicable |
| Cleaning Blades | Not applicable |
| Yield | Not applicable |
| Other | Not applicable |
| Yield | Not applicable |
| Fuser Oil | Not required |
| PM Schedule | 300,000 |
| SUPPLIES | |
| Photoconductor | Intermediate masters |
| Yield | 5,000/master* |
| Price | Priced by dealer |
| Toner | 1,000-cc ink ctrdg |
| Yield | 16,500 |
| % Coverage | 6% |
| Price | Priced by dealer |
| Developer | Not applicable |
| Yield | Not applicable |
| Price | Not applicable |
| MULTIFUNCTION MODES | |
| Copier | Std |
| Internet Fax | No |
| Network Printer | Opt |
| Printer | Opt |
| Fax | No |
| Network Fax | No |
| PC Fax | No |
| Scanner | No |
| CONNECTIVITY SPECIFICATIONS | |
| Operating System Support | Mac 7.5+, Win 3.11, 9.x, NT 4.0** |
| Parallel Interface | Opt |
| PC Fax/Print/Scan | No/Yes/No |
| Serial Interface | None |
| PC Fax/Print/Scan | Not applicable |
| USB Interface | None |
| PC Fax/Print/Scan | Not applicable |
| Network Interface | Opt Ethernet |
| Interface Type | 10/100BaseT |

| | |
|---------------------------------|------------------------------------|
| LAN Fax/Print/Scan | No/Yes/No |
| Networks Supported | |
| NetWare | Yes |
| Windows NT | Yes |
| AppleTalk | Yes |
| UNIX | No |
| AS/400 | No |
| Other | Info not avail |
| FACSIMILE SPECIFICATIONS | |
| Scanner Technology | Not applicable |
| Compression Method | Not applicable |
| Modem Speed | Not applicable |
| Max TX Resolution | Not applicable |
| Gray Scale/Halftones | Not applicable |
| Std/Max Fax Memory | Not applicable |
| Min/Max Orig Size (WxL) | Not applicable |
| Max Paper/Print Width | Not applicable |
| Effective Scanning Width | Not applicable |
| Correct-Order Output | Not applicable |
| Batch Files | Not applicable |
| Battery Backup | Not applicable |
| Confid TX/RX | Not applicable |
| Dual Lines | Not applicable |
| Multi Access | Not applicable |
| Polling | Not applicable |
| Relay Request | Not applicable |
| Smoothing | Not applicable |
| Timers | Not applicable |
| Transfer Hub | Not applicable |
| DIALING CAPABILITIES | |
| Broadcasting (Groups/Dest) | Not applicable |
| Redial (Attempts/Intervals) | Not applicable |
| One Touch | Not applicable |
| Speed Dial | Not applicable |
| Other | |
| PRINTER SPECIFICATIONS | |
| Engine Mfr & Model | Ricoh/Priport JP5000 |
| Compatibility | IBM PC, Mac |
| Speed | 60, 90, 120 ppm |
| Max Print Area | 11.4 x 16.5 |
| Enhanced Resolution | Not applicable |
| Unenhanced Resolution | 400 x 400 dpi |
| Std/Max Printer Memory | 64 MB, 2-GB HDD/64 MB, 2-GB HDD*** |
| Controller Mfr/Model | SMA/UC6 |
| Processor/Bits/MHz | Cyrix M3-500/Info not avail/500 |
| PDL/PCL | PostScript 2 |
| Controller Mfr/Model | SMA/UC5, UC5e**** |
| Processor/Bits/MHz | Info not avail |
| PDL/PCL | Windows GDI |
| Controller Mfr/Model | Not applicable |

| | |
|--|--|
| Processor/Bits/MHz | Not applicable |
| PDL/PCL | Not applicable |
| Other | ***UC6 controller std/max memory; ****UC5, UC5e controller std/max memory, 16 MB; remote copy setting; auto on-line; image overlay |
| SCANNER AND IMAGE MANAGEMENT SPECIFICATIONS | |
| Connection Type | Not applicable |
| Technology/Speed | Not applicable |
| Max Resolution | Not applicable |
| TWAIN Compatible | Not applicable |
| Scan Destinations | |
| E-mail | NA |
| I-fax | INA |
| FTP | INA |
| SMB | INA |
| HDD | INA |
| URL | INA |
| LDAP Support | Info not avail |
| Scan/Image Software | Not applicable |
| OCR Software | Not applicable |
| File Mgmt Software | Not applicable |
| COMMENTS | |
| | **Also 2000 and Me |
| CONNECTIVITY/MF OPTIONS | |
| | UC6 print controller: \$3,695 UC5 print controller: \$1,515 UC5e print controller: \$1,290 Type 10 interface kit: \$96 |