

Ricoh Aficio 1055

BACKGROUND INFORMATION	12630/USA
Dataquest Segment	4
SRP	\$17,000
Manufacturing Status	Discontinued (08/2005)
Domestic Intro Date	November 2002
OEM	Ricoh (Japan)
Also Sold As	Gestetner 5502; Lanier LD055; Savin 2555
Distributed By	Dealers, branches and subsidiaries
Max Monthly Duty Cycle	175,000 impressions
TYPE	Monochrome copier, MF
Configuration/Scanner	Console,digital
Toner	Dry, dual component
GENERAL SPECIFICATIONS/PAPER HANDLING	
First Copy Time	3.5 sec
Multicopy (Ltr/Lgl/Ldgr)	55/37/28 cpm
Warm-up Time	5.5 min
Std Paper Source(s)	Triple drawer*
Std Paper Capacity	1,550/1,550/550/550 sheets
Paper Weights	14 to 34 lbs
Bypass/Paper Weights	50-sheet/14-lb bond to 90-lb index
Max Paper Sources	5
Max Paper Capacity	7,750 sheets
Max Original Size	11 x 17
Output Size (Min/Max)	5-1/2 x 8-1/2/11 x 17
Copy Resolution	600 x 600 dpi
Copier Memory (Std/Max)	48 MB, 20-GB HD/256 MB, 20-GB HD
Duplex	Auto (1:2,2:2,2:1)
Duplex Capacity/Paper Sizes	Unlimited/5-1/2 x 8-1/2 to 11 x 17
Document Feeder	Std RADF
Doc Feeder Speed/Capacity	55 opm/100 orig
Paper Weights	11 to 34 lbs
Sorter (Bins/Capacity)	None
Staple Sorter	None
Bins/Stapling Capacity	Not applicable
Stapling Positions	Not applicable
Finisher	Opt finisher
Tray/Stapling/Position(s)	3,250/50/4
Other	
SECURITY SPECS	
Network User Authentication	Info not avail
IP Address Filtering	Info not avail
MAC Address Filtering	Info not avail
HDD Overwrite	Info not avail
Max Overwrites	Info not avail
HDD Encryption	Info not avail

Secure Print	Info not avail
Other	
CONTROL PANEL	Keypad and touch screen
Quantity Selector	1 to 999 (0 to 9 keypad)
Message Display	Yes
Help Key	No
FEATURES	
Automatic Features	AES, AMS, APS, ATS, AS
Book Copy	Yes
Booklet Mode	Std
Color	No
Copy Control	500
Covers	Std
Editing	No
Energy-Save	Yes
Erase	Std
Image Insert	No
Image Overlay	No
Image Repeat	Yes
Image Rotate	Std
Interrupt	Yes
Job Build	Yes
Job Programs	10
Job Time	Yes
Language	Std
Margin Shift	Yes
Neg/Pos	No
OHP Interleaving	Yes
Photo Mode	Yes
Poster Mode	No
Preset R/E	6R,5E
Program Ahead	Std
Sheet Insertion	Std
Stamping	Std
Timer	Yes
2-in-1	Std
XY Zoom	Yes
Zoom Range	25 to 400 (1%)
Other Features	*Tandem drawers
ADDITIONAL INFORMATION	
Dimensions (HxWxD)	44.9" x 27.2" x 29.6"
Weight	414.5 lbs
Power Requirements	120 V, 20 A
Dedicated Outlet	Required
Energy Star Compliant	Yes
Operating Noise Level	70 dB
COMMENTS	Opt Connect Copy (tandem copying)
OPTIONS	
	3,500-sheet LCT: \$1,832 Finisher: \$2,880

	2-hole/3-hole punch kit: \$875/\$875 8-1/2 x 14 tray: \$810 Copy tray: \$145 Copy Connect: \$2,200
MAINTENANCE	
Fuser Rollers	Two
Yield	Info not avail
Cleaning Blades	Drum
Yield	Info not avail
Other	Not applicable
Yield	Not applicable
Fuser Oil	Not required
PM Schedule	150,000
SUPPLIES	
Photoconductor	Organic drum
Yield	360,000
Price	Priced by dealer
Toner	Ctrdg weight not avail
Yield	46,000
% Coverage	6%
Price	Priced by dealer
Developer	Btl weight not avail
Yield	300,000
Price	Priced by dealer
MULTIFUNCTION MODES	
Copier	Std
Internet Fax	No
Network Printer	Opt
Printer	Opt
Fax	No
Network Fax	No
PC Fax	No
Scanner	No
CONNECTIVITY SPECIFICATIONS	
Operating System Support	Mac, 8.6+, Win 9x, NT 4.0, 2000**
Parallel Interface	Std
PC Fax/Print/Scan	No/Yes/No
Serial Interface	None
PC Fax/Print/Scan	Not applicable
USB Interface	None
PC Fax/Print/Scan	Not applicable
Network Interface	Opt Ethernet
Interface Type	10/100BaseT
LAN Fax/Print/Scan	No/Yes/No
Networks Supported	
NetWare	Yes
Windows NT	Yes
AppleTalk	Yes
UNIX	TBA
AS/400	TBA

Other	
FACSIMILE SPECIFICATIONS	
Scanner Technology	Not applicable
Compression Method	Not applicable
Modem Speed	Not applicable
Max TX Resolution	Not applicable
Gray Scale/Halftones	Not applicable
Std/Max Fax Memory	Not applicable
Min/Max Orig Size (WxL)	Not applicable
Max Paper/Print Width	Not applicable
Effective Scanning Width	Not applicable
Correct-Order Output	Not applicable
Batch Files	Not applicable
Battery Backup	Not applicable
Confid TX/RX	Not applicable
Dual Lines	Not applicable
Multi Access	Not applicable
Polling	Not applicable
Relay Request	Not applicable
Smoothing	Not applicable
Timers	Not applicable
Transfer Hub	Not applicable
DIALING CAPABILITIES	
Broadcasting (Groups/Dest)	Not applicable
Redial (Attempts/Intervals)	Not applicable
One Touch	Not applicable
Speed Dial	Not applicable
Other	
PRINTER SPECIFICATIONS	
Engine Mfr & Model	Ricoh/Aficio 1055
Compatibility	IBM PC, Mac
Speed	55 ppm
Max Print Area	11 x 17
Enhanced Resolution	2400 x 600 dpi
Unenhanced Resolution	600 x 600 dpi
Std/Max Printer Memory	32 MB, 6-GB HD/256 MB, 6-GB HD
Controller Mfr/Model	Ricoh/Print controller Type 1055
Processor/Bits/MHz	Info not avail/Info not avail/266
PDL/PCL	PCL 5e/6, opt Adobe PostScript 3
Controller Mfr/Model	Not applicable
Processor/Bits/MHz	Not applicable
PDL/PCL	Not applicable
Controller Mfr/Model	Not applicable
Processor/Bits/MHz	Not applicable
PDL/PCL	Not applicable
Other	Booklet mode; cover mode; transparency inter-leaving; proof copy
SCANNER AND IMAGE MANAGEMENT SPECIFICATIONS	
Connection Type	Not applicable

Technology/Speed	Not applicable
Max Resolution	Not applicable
TWAIN Compatible	Not applicable
Scan Destinations	
E-mail	NA
I-fax	INA
FTP	INA
SMB	INA
HDD	INA
URL	INA
LDAP Support	Info not avail
Scan/Image Software	Not applicable
OCR Software	Not applicable
File Mgmt Software	Not applicable
COMMENTS	
	**Also Me & XP
CONNECTIVITY/MF OPTIONS	
	Print controller Type 1055: \$2,455 Adobe PostScript 3: \$2,055 Network interface card: \$499 32-MB printer memory: \$240 64-MB printer memory: \$345 128-MB printer memory: \$600 GlobalScan One (supports 1 MFP): \$1,995 GlobalScan 5 (supports 5 MFPs): \$4,995 GlobalScan 25 (supports 25 MFPs): \$10,995 GlobalScan 100 (supports 100 MFPs): \$29,495 GlobalScan 5 MFP Add-On Client: \$2,995 GlobalScan OCR: \$2,995 GlobalScan RightFax option: \$1,995