

# Ricoh Priport JP 1230

<b>BACKGROUND INFORMATION</b>	<b>12255/USA</b>
Dataquest Segment	NA
SRP	\$6,175
Manufacturing Status	Discontinued (03/2003)
Domestic Intro Date	September 2000
OEM	Ricoh (Japan)
Also Sold As	Gestetner CopyPrinter 5308L; Lanier LDD 020; Savin 3150eDNP; Standard SD330
Distributed By	Dealers, branches and subsidiaries
Max Monthly Duty Cycle	300,000 impressions
<b>TYPE</b>	<b>Digital duplicator, MF</b>
Configuration/Scanner	Desktop, digital
Toner	Ink technology
<b>GENERAL SPECIFICATIONS/PAPER HANDLING</b>	
First Copy Time	27 sec
Multicopy (Ltr/Lgl/Ldgr)	80 to 130/80 to 130/80 to 130 cpm
Warm-up Time	None
Std Paper Source(s)	Single tray
Std Paper Capacity	1,000 sheets
Paper Weights	13-lb bond to 110-lb index
Bypass/Paper Weights	None
Max Paper Sources	1
Max Paper Capacity	1,000 sheets
Max Original Size	10.1 x 14.3
Output Size (Min/Max)	3-5/8 x 5.9/8-1/2 x 14
Copy Resolution	300 x 300 dpi
Copier Memory (Std/Max)	Not applicable
Duplex	Manual
Duplex Capacity/Paper Sizes	Not applicable
Document Feeder	Opt ADF
Doc Feeder Speed/Capacity	Not applicable/30 orig
Paper Weights	13 to 23 lbs
Sorter (Bins/Capacity)	None
Staple Sorter	None
Bins/Stapling Capacity	Not applicable
Stapling Positions	Not applicable
Finisher	None
Tray/Stapling/Position(s)	Not applicable
Other	
<b>SECURITY SPECS</b>	
Network User Authentication	Info not avail
IP Address Filtering	Info not avail
MAC Address Filtering	Info not avail
HDD Overwrite	Info not avail

Max Overwrites	Info not avail
HDD Encryption	Info not avail
Secure Print	Info not avail
Other	
<b>CONTROL PANEL</b>	<b>Keypad</b>
Quantity Selector	1 to 9,999 (0 to 9 keypad)
Message Display	Yes, 40 characters
Help Key	No
<b>FEATURES</b>	
Automatic Features	AES
Book Copy	No
Booklet Mode	No
Color	Opt
Copy Control	20
Covers	No
Editing	No
Energy-Save	Yes
Erase	Std
Image Insert	No
Image Overlay	No
Image Repeat	No
Image Rotate	Std
Interrupt	No
Job Build	No
Job Programs	9
Job Time	No
Language	Std
Margin Shift	Yes
Neg/Pos	No
OHP Interleaving	No
Photo Mode	Yes
Poster Mode	No
Preset R/E	4R,3E
Program Ahead	No
Sheet Insertion	No
Stamping	No
Timer	No
2-in-1	No
XY Zoom	No
Zoom Range	None
Other Features	Platen-type duplicator; edge/center/shadow erase; inter- active LCD display; tint mode; skip-feed mode; auto cycle mode; line mode; line/photo mode; security mode; economy mode; max print area, 8.2" x 13.9"; class and program mode; fine mode (300 x 400 dpi); nine languages
<b>ADDITIONAL INFORMATION</b>	
Dimensions (HxWxD)	25" x 27" x 25"
Weight	143 lbs
Power Requirements	120 V, 3 A
Dedicated Outlet	Not required
Energy Star Compliant	No

Operating Noise Level	70 dB
COMMENTS	Options incl color drum, CPIF -20 and CPIF-26 controllers, Windows, ADF, tape dispenser and cabinet; *260 masters/ roll; colors avail: red, green, blue, brown, navy, teal, purple, orange, yellow, maroon; adj copy speed (3 speeds); waste container holds 40 used masters
<b>OPTIONS</b>	
	ADF: \$1,138 Tape dispenser: \$330 Color drum: \$1,025 Cabinet: \$288
<b>MAINTENANCE</b>	
Fuser Rollers	Not applicable
Yield	Not applicable
Cleaning Blades	Not applicable
Yield	Not applicable
Other	Not applicable
Yield	Not applicable
Fuser Oil	Not required
PM Schedule	350,000
<b>SUPPLIES</b>	
Photoconductor	Intermediate masters
Yield	5,000/master*
Price	Priced by dealer
Toner	600-cc ink ctrdg
Yield	7,000
% Coverage	6%
Price	Priced by dealer
Developer	Not applicable
Yield	Not applicable
Price	Not applicable
<b>MULTIFUNCTION MODES</b>	
Copier	Std
Internet Fax	No
Network Printer	Opt
Printer	Opt
Fax	No
Network Fax	No
PC Fax	No
Scanner	No
<b>CONNECTIVITY SPECIFICATIONS</b>	
Operating System Support	Mac 7.5+, Win 3.11, 9.x**
Parallel Interface	Opt
PC Fax/Print/Scan	No/Yes/No
Serial Interface	None
PC Fax/Print/Scan	Not applicable
USB Interface	None
PC Fax/Print/Scan	Not applicable
Network Interface	Opt Ethernet
Interface Type	10/100BaseT

LAN Fax/Print/Scan	No/Yes/No
Networks Supported	
NetWare	Yes
Windows NT	Yes
AppleTalk	Yes
UNIX	No
AS/400	No
Other	Info not avail
<b>FACSIMILE SPECIFICATIONS</b>	
Scanner Technology	Not applicable
Compression Method	Not applicable
Modem Speed	Not applicable
Max TX Resolution	Not applicable
Gray Scale/Halftones	Not applicable
Std/Max Fax Memory	Not applicable
Min/Max Orig Size (WxL)	Not applicable
Max Paper/Print Width	Not applicable
Effective Scanning Width	Not applicable
Correct-Order Output	Not applicable
Batch Files	Not applicable
Battery Backup	Not applicable
Confid TX/RX	Not applicable
Dual Lines	Not applicable
Multi Access	Not applicable
Polling	Not applicable
Relay Request	Not applicable
Smoothing	Not applicable
Timers	Not applicable
Transfer Hub	Not applicable
<b>DIALING CAPABILITIES</b>	
Broadcasting (Groups/Dest)	Not applicable
Redial (Attempts/Intervals)	Not applicable
One Touch	Not applicable
Speed Dial	Not applicable
Other	
<b>PRINTER SPECIFICATIONS</b>	
Engine Mfr & Model	Ricoh/Priport JP1230
Compatibility	IBM PC, Mac
Speed	80 to 130 ppm
Max Print Area	8.2 x 13.9
Enhanced Resolution	Not applicable
Unenhanced Resolution	300 x 300 dpi
Std/Max Printer Memory	64 MB, 2-GB HDD/64 MB, 2-GB HDD***
Controller Mfr/Model	SMA/UC6
Processor/Bits/MHz	Cyrix M3-500/Info not avail/500
PDL/PCL	PostScript 2
Controller Mfr/Model	SMA/UC5, UC5e****
Processor/Bits/MHz	Info not avail
PDL/PCL	Windows GDI
Controller Mfr/Model	Not applicable

Processor/Bits/MHz	Not applicable
PDL/PCL	Not applicable
Other	***UC6 controller std/max memory; ****UC5/UC5e controller std/max memory, 16 MB; remote copy setting; auto on-line; image overlay
<b>SCANNER AND IMAGE MANAGEMENT SPECIFICATIONS</b>	
Connection Type	Not applicable
Technology/Speed	Not applicable
Max Resolution	Not applicable
TWAIN Compatible	Not applicable
Scan Destinations	
E-mail	NA
I-fax	NA
FTP	NA
SMB	NA
HDD	NA
URL	NA
LDAP Support	Info not avail
Scan/Image Software	Not applicable
OCR Software	Not applicable
File Mgmt Software	Not applicable
<b>COMMENTS</b>	
	**Also NT 4.0, 2000, Me and XP
<b>CONNECTIVITY/MF OPTIONS</b>	
	UC6 print controller: \$3,695 UC5 print controller: \$1,515 UC5e print controller: \$1,290 Type 15 interface kit: \$96